


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
1	WAS CLOSED TOOL	7/13/11	BTH



SECTION A - A

$A_0 = 2.10$
 $B_0 = 6.50$
 $K_0 = 0.60$

NOTES:

1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE ± 0.2
2. POCKET POSITION RELATIVE TO SPROCKET HOLE MEASURED AS TRUE POSITION OF POCKET, NOT POCKET HOLE
3. A_0 AND B_0 ARE CALCULATED ON A PLANE AT A DISTANCE "R" ABOVE THE BOTTOM OF THE POCKET.



ADVANTEK[®]
engineered confidence™

TITLE ADVANTEK PART DRAWING NUMBER BBA001-A CARRIER TAPE			
TOLERANCES - UNLESS NOTED 1PL ± 0.2 2PL ± 0.10		MATERIAL PS+C	DWG SIZE B
ALL DIMS IN MILLIMETERS PER ASME Y14.5M			
DRAWN BY NCE	DATE 04/01/2005	SCALE 4:1	SHEET 1 OF 1
CK'D BY	PROJECT NO. 17.00/ 7417.00	DWG NO. T105058BT	REV 1